

APD 33 A

Aksa
Aksa P 602

Manufacturer		Aksa			
Model		A4CRX25T			
		<table border="1"> <tr> <td>% \$ \$ ' "# "</td> </tr> <tr> <td>&- ž+\$' "</td> </tr> <tr> <td>0-ž \$<DQ</td> </tr> </table>	% \$ \$ ' "# "	&- ž+\$' "	0-ž \$<DQ
% \$ \$ ' "# "					
&- ž+\$' "					
0-ž \$<DQ					
	L	2,540			
	"	90 X 95			
		18.0:1			
	fl # ı	"# " 1500			
	fl ı	L 8,50			
	L	11,00			
AbsorbedAirDischargeReSourceKey.Text	' # "	2,40			
	' # "	115,00			
	' # "	6,10			
	° C	420,00			
		12 V d.c.			
	Load	%\$ \$ı			
	# "	6,80			

		Aksa
		AK225
	Hz	50
	"	31,30
		3
	fl ı	400/230
	A	45,00

		fl ı		fl ı	
	"	"	"	"	L
APD 33 A	680,00	1500,00	900,00	1060,00	95,00
		fl ı		fl ı	
	"	"	"	"	L
ASM 3	800.00	1940	970	1220	95

APD 33 A

Aksa
Aksa P 602

9B: 9B
9b[]bY'gdYYX"
C]'dfYggi fY"
7cc'UbhY'a dYfUhi fY"
F i b' hja Y"
6UHYfmj c'rg"
7cbZ[i fUVY' hja]b["
; 9B9F 5HCF
J c' hU[Y f@ @B' "
7i ffYbhf@&!@ E"
: fYei YbVW"
A 5-BG
J c' hU[Y f@ @B' "
: fYei YbVW"
A U]bg'fYUXn'
A U]bg'YbUV'YX"
; Yb"GYhfYUXn'
; Yb"GYhYbUV'YX"

K 5F B-B;
7\Uf[Y Z]i fY"
6UHYfm@ck #][\] c' hU[Y"
: U] 'hc' ghcd"
@ck #][\ [YbYfUhc'f] c' hU[Y"
I bXYf#j Yf[YbYfUhc'f] fYei YbVW"
Cj Yf# bXYf'gdYYX"
@ck c]'dfYggi fY"
<][\ V'c'UbhY'a dYfUhi fY"
G<I H8CK BG
: U] 'hc' ghUf"
9a Yf[YbVW'ghcd"
@ck c]'dfYggi fY"
<][\ V'c'UbhY'a dYfUhi fY"
Cj Yf# bXYf'gdYYX"
I bXYf#j Yf[YbYfUhc'f] fYei YbVW"
I bXYf#j Yf[YbYfUhc'f] c' hU[Y"
C]'dfYggi fY'gYbgcf'cdYb"
7cc'UbhY'a dYfUhi fY'gYbgcf'cdYb"
9@97 HF =75@HF -D
: YbYfUhc'f] YfW'ffYbh'

: 'YI J'V'Y'gYbgcf'WVb VY V'c'bfcc'YX'k]h' h'Ya dYfUhi fYz
dfYggi fYz dYfVW'bhU[Y f'k Ufb]b[#]i h'Xck b# 'YVW'VW' h'f]dL
@c'WV'gYh]b['dUfUa YHfg'UbX'a cb]h'f]b['Zca 'D7' hc
V'c'bfcc' a cXi 'Y'k]h' I G6 V'c'bbYVW]cb'fa Ul '* 'a H'

9'YVW]VW' GUZYhm#9A 7 'V'a dUfV]]hm6G'9B '* \$-) \$
9'YVW]VW' Vi g]bYgg'Yei]da Ybh'
6G'9B '*%\$!*&9A 7 'ja a i b]mighUbXUfX"
6G'9B '*%\$!*('9A 7 'Ya]gg]cb'ghUbXUfX"

'6UHYfmVWUf[Yf]g'a Ubi ZVW' fYX'k]h' 'gk]h'W]b[!a cXY'UbX'GA 8 'YVW'bc'c[mUbX'ih\Ug\][\ YZ]V]bYVW' 6UHYfmVWUf[Yf
a cXY'gfci hdi hJ !=VWUfUWVf]gh]W]g'j YfmV'cgY'hc'gei UfY'UbX'ci hdi h]g']'Ua dYfz% z']'Zcf'%&j'c'hUbX'&+Z']'Zcf'&'(]'
#bdi h% , ' !&* (j c'h57 "'Dfc]bY'&(\$) \Ug'Z' mci hdi hg\chV]VW]hdfchV]cb'UbX'ihVWb'VY'i gYX'Ug'U'VW'ffYbhgci fVW"
Dfc]bY'%&\$) #&(\$) V'WUf[Yf'\Ug'\][\ YZ]V]bYVW'cb["]Z'Z' 'ck ZU]i fY'fUfYz'][\ hk Y][\ hUbX' 'ck \ YUhfUX]UfYX']b
U'V'c'fXUbW'k]h']'bYUf'U'fYbU]h'j Yg' H\Y'VWUf[Yf]g'Z]h'YX'k]h' U'dfchV]cb'X]cXY'U'V'cgg'h'Y'ci hdi h'7 cbbYVWVWUf[Y'Z]
fY'UmV'c] VY'hk Y'Yb'dcg]h]j Y'ci hdi hUbX'7: 'ci hdi h' H\Y'mUfY'Yei]ddYX'k]h' F: =Z]h'f'hc'fYXi V'Y'YVW]VW'bc]gY'fUX]UfYX
Zca 'h'Y'XY'jVW"; U] Ub]VW' m]gc'UfYX']bdi hUbX'ci hdi h]m]d]VW'm(_J'Zcf'\][\ fY']UV]]m'

APD 33 A

Aksa
Aksa P 602

5GA " !'



- 1 Steel structures.
- 2 Emergency stop push button.
- 3 Control panel is mounted on the baseframe . Located at the right side of the generator set
- 4 Corrosion-resistant locks and hinges.
- 5 oil could be drained via valve and a hose
- 6 Exhaust system in the canopy.
- 7 special large access doors for easy maintenance
- 8 Base frame -fuel tank.
- 9 Lifting Points.
- 10 sound proofing materials.

f) !&+)

ž

ž

ž

ž

ž

ž

ž

	"	970
f) "L	"	1940
f) "L	"	1220
	L	95